Rittal – The System.

Faster – better – everywhere.

Side panels, divided with lockable quickrelease fastener, for TS IT – DK 5501.030

Date : Aug 10, 2016



ENCLOSURES

POWER DISTRIBUTION 📎 CLIMATE CONTROL

>> IT INFRASTRUCTURE >>> SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Side panels, divided with lockable quick-release fastener, for TS IT – DK 5501.030

created: 10.08.2016 on www.rittal.com/com-en



Product description

Benefits:Easy to use Tool-free assembly Internal latch included (cannot be opened with a key)Material:Sheet steelSurface finish:Spray-finishedColour:RAL 7035Supply includes:Console Pedestal Earth conductor Assembly partsPacks of:1 pc(s).EAN:4028177678729Customs tariff number:94032080eCl@ss 5.1:27182101ETIM 6.0:Eco02524		
Surface finish:Spray-finishedColour:RAL 7035Supply includes:Console Pedestal Earth conductor Assembly partsPacks of:1 pc(s).EAN:4028177678729Customs tariff number:94032080eCl@ss 5.1:27182101eCl@ss 7.0:27182101	Benefits:	Tool-free assembly
Colour:RAL 7035Supply includes:Console Pedestal Earth conductor Assembly partsPacks of:1 pc(s).EAN:4028177678729Customs tariff number:94032080eCl@ss 5.1:27182101eCl@ss 7.0:27182101	Material:	Sheet steel
Supply includes:Console Pedestal Earth conductor Assembly partsPacks of:1 pc(s).EAN:4028177678729Gustoms tariff number:94032080eCl@ss 5.1:27182101eCl@ss 7.0:27182101	Surface finish:	Spray-finished
Pedestal Earth conductor Assembly partsPacks of:1 pc(s).EAN:4028177678729Customs tariff number:94032080eCl@ss 5.1:27182101ECl@ss 7.0:27182101	Colour:	RAL 7035
EAN: 4028177678729 Customs tariff number: 94032080 eCl@ss 5.1: 27182101 eCl@ss 7.0: 27182101	Supply includes:	Pedestal Earth conductor
Customs tariff number: 94032080 eCl@ss 5.1: 27182101 eCl@ss 7.0: 27182101	Packs of:	1 pc(s).
number: eCl@ss 5.1: 27182101 eCl@ss 7.0: 27182101	EAN:	4028177678729
eCl@ss 7.0: 27182101		94032080
	eCl@ss 5.1:	27182101
ETIM 6.0: EC002524	eCl@ss 7.0:	27182101
	ETIM 6.0:	EC002524

Product features	
To fit:	Enclosure type: TS IT Height: = 2000 mm Depth: = 1000 mm
Weight/pack:	17 kg
Downloads	
Documentation:	Instructions (FR, NL, IT, JP, DE, EN)
CAD drawings:	Request