

Rittal – The System.

Faster – better – everywhere.

► Slide rails, depth- variable for TS IT, TE – DK 5501.460

Date : Aug 11, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Slide rails, depth-variable for TS IT, TE – DK 5501.460

created: 11.08.2016 on www.rittal.com/com-en



Product description

Benefits:	Tool-free, time-saving one-man assembly from the enclosure front All three mounting holes in the EIA system punchings are available for screw-fastening the equipment. Alternatively, direct screw fastening to the 482.6 mm (19") system punchings is also possible
Applications:	For mounting between the front and the rear pair of mounting angles To support heavy installed equipment To adapt to individual distances between 482.6 mm (19") levels
Material:	Sheet steel
Surface finish:	Zinc-plated
Supply includes:	Assembly parts
Note:	Effective contact surface 25 mm per side
Packs of:	2 pc(s).
EAN:	4028177679016
Customs tariff number:	73269098
eCl@ss 5.1:	27182504
eCl@ss 7.0:	27182590
ETIM 6.0:	EC002620

Product features

To fit: Enclosure type: TS IT
Enclosure type: TE 7000

Installation options: 482.6 mm (19") L mounting angles, front and rear
482.6 mm (19") mounting frames front and rear

Distance between levels: min.: 400 mm
max.: 600 mm

Contact surface: Width: 25 mm

Load capacity: 80 kg

Weight/pack: 2.36 kg

Downloads

Documentation:  [Instructions](#)

CAD drawings: Request