

# Rittal – The System.

Faster – better – everywhere.

► **Network/server enclosures TS IT with glazed door, with 482.6 mm (19") mounting angles – DK 5510.120**

Date : Aug 10, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Network/server enclosures TS IT with glazed door, with 482.6 mm (19") mounting angles – DK 5510.120

created: 10.08.2016 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description


|                         |  |
|-------------------------|--|
| <b>Material:</b>        | Sheet steel<br>Aluminium<br>Glazed door: Single-pane safety glass, 3 mm  |
| <b>Surface finish:</b>  | Enclosure frame: Dipcoat-primed<br>Interior installation: Dipcoat-primed<br>Doors and roof: Dipcoat-primed, powder-coated  |
| <b>Colour:</b>          | Enclosure frame and panels: RAL 7035<br>Interior installation: RAL 9005  |
| <b>Supply includes:</b> | TS 8 enclosure frame with doors and roof plate<br>Glazed aluminium door at the front, 180° hinges<br>Lock front and rear: Comfort handle for semi-cylinders and security lock 3524 E<br>Two 482.6 mm (19") mounting sections front and rear, variably mounted on support strips with quick-release fasteners<br>Spacers to raise the fan cover plate, for passive cooling (supplied loose)<br>Connection accessories for potential equalisation with earthing point (supplied loose)<br>50 multi-tooth screws M5, cage nuts M5, conductive (supplied loose)<br>IPPC pallet<br>1 Roof plate, multi-piece, removable, with side cable entry in the depth and covered cut-out for fan mounting plate<br>1 Sheet steel door at the rear, vertically divided, 180° hinges |
| <b>Note:</b>            | Depending on the siting type and location, the door opening may vary for selected applications   |
| <b>Packs of:</b>        | 1 pc(s).   |
| <b>EAN:</b>             | 4028177678569  |

|                               |             |
|-------------------------------|-------------|
| <b>Customs tariff number:</b> | 94032080    |
| <b>eCl@ss 5.1:</b>            | 27180201    |
| <b>eCl@ss 7.0:</b>            | 27180207    |
| <b>ETIM 6.0:</b>              | EC002499    |
| <b>Basic material:</b>        | Sheet steel |





## Product features

|  |  |
|--|--|
| <b>Dimensions:</b>                           | Width: 600 mm<br>Height: 2000 mm<br>Depth: 1200 mm |
| <b>Installation height for components:</b>   | 42 U   |
| <b>Distance between levels as delivered:</b> | 745 mm   |
| <b>Load capacity:</b>                        | 482.6 mm (19") level: 15000 N                      |
| <b>Weight/pack:</b>                          | 103.2 kg   |

## Approvals

|                   |  |
|-------------------|--|
| <b>Approvals:</b> |  <a href="#">UL + C-UL (EN)</a> |
|-------------------|--|

## Downloads

|                       |   |
|-----------------------|---|
| <b>Data sheets:</b>   |  <a href="#">Technical details EN</a><br> <a href="#">Technical system catalogue (DE)</a> |
| <b>Documentation:</b> |  <a href="#">Instructions (FR, EN, DE)</a>   |
| <b>CAD drawings:</b>  |  <a href="#">Visio Shapes (EN, DE)</a>   |
| <b>CAD drawings:</b>  | Request   |