

# Rittal – The System.

Faster – better – everywhere.

► **Network/server enclosures TS IT with glazed door, IP 55, with 482.6 mm (19") mounting frame – DK 5514.131**

Date : Aug 10, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Network/server enclosures TS IT with glazed door, IP 55, with 482.6 mm (19") mounting frame – DK 5514.131

created: 10.08.2016 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description



<b>Material:</b>	Sheet steel Aluminium Glazed aluminium door with 3 mm single-pane safety glass
<b>Surface finish:</b>	Enclosure frame: Dipcoat-primed Interior installation: Dipcoat-primed Doors and roof: Dipcoat-primed, powder-coated
<b>Colour:</b>	Enclosure frame and panels: RAL 7035 Interior installation: RAL 9005
<b>Protection category IP to IEC 60 529:</b>	IP 55 only in conjunction with baying seal or screw-fastened side panels
<b>Supply includes:</b>	TS 8 enclosure frame with doors and roof plate Glazed aluminium door at the front, 180° hinges Sheet steel door at the rear, 180° hinges Lock front and rear: Comfort handle for semi-cylinders and security lock 3524 E Roof plate, one-piece, solid Base tray and gland plate, multi-piece, solid Two 482.6 mm (19") mounting frames, front and rear, depth-variable Baying seal and sealing kit for gland plates (supplied loose) Connection accessories for potential equalisation with earthing point (supplied loose) 50 multi-tooth screws M5, cage nuts M5, conductive (supplied loose) IPPC pallet
<b>Note:</b>	Depending on the siting type and location, the door opening may vary for selected applications For enclosures with height and depth 2000 x 1200 mm / 2200 x 1000 mm / 2200 x 1200 mm, the matching side panels are optionally available and are supplied fitted to the enclosure
<b>Packs of:</b>	1 pc(s).

<b>EAN:</b>	4028177705760
<b>Customs tariff number:</b>	94032080
<b>eCl@ss 5.1:</b>	27180201
<b>eCl@ss 7.0:</b>	27180207
<b>ETIM 6.0:</b>	EC002499
<b>Basic material:</b>	Sheet steel





## Product features

<b>Dimensions:</b>	Width: 800 mm Height: 2200 mm Depth: 1000 mm
<b>Installation height for components:</b>	47 U
<b>Distance between levels as delivered:</b>	745 mm
<b>Load capacity:</b>	482.6 mm (19") level: 10000 N
<b>Weight/pack:</b>	139 kg

## Approvals

<b>Approvals:</b>	
<b>Certificates:</b>	

## Downloads

<b>Data sheets:</b>	 <a href="#">Technical details (DE)</a>  <a href="#">Technical system catalogue (DE)</a>
<b>Documentation:</b>	 <a href="#">Instructions (FR, EN, DE)</a>
<b>CAD drawings:</b>	 <a href="#">Visio Shapes (EN, DE)</a>
<b>CAD drawings:</b>	Request