

Rittal – The System.

Faster – better – everywhere.

► **Network/server enclosures TS IT with glazed door, with 482.6 mm (19") mounting angles – DK 5527.120**

Date : Aug 10, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Network/server enclosures TS IT with glazed door, with 482.6 mm (19") mounting angles – DK 5527.120

created: 10.08.2016 on www.rittal.com/com-en



Product description


| | |
|-------------------------|--|
| Material: | Sheet steel Aluminium Glazed door: Single-pane safety glass, 3 mm |
| Surface finish: | Enclosure frame: Dipcoat-primed Interior installation: Dipcoat-primed Doors and roof: Dipcoat-primed, powder-coated |
| Colour: | Enclosure frame and panels: RAL 7035 Interior installation: RAL 9005 |
| Supply includes: | TS 8 enclosure frame with doors and roof plate Glazed aluminium door at the front, 180° hinges Lock front and rear: Comfort handle for semi-cylinders and security lock 3524 E Two 482.6 mm (19") mounting sections front and rear, variably mounted on support strips with quick-release fasteners Spacers to raise the fan cover plate, for passive cooling (supplied loose) Connection accessories for potential equalisation with earthing point (supplied loose) 50 multi-tooth screws M5, cage nuts M5, conductive (supplied loose) IPPC pallet 1 Roof plate, multi-piece, removable, for horizontal cable entry at the rear and covered cut-out for fan mounting plate 1 Sheet steel door at the rear, vertically divided, 180° hinges |
| Note: | Depending on the siting type and location, the door opening may vary for selected applications |
| Packs of: | 1 pc(s). |
| EAN: | 4028177702721 |

| | |
|-------------------------------|-------------|
| Customs tariff number: | 94032080 |
| eCl@ss 5.1: | 27180201 |
| eCl@ss 7.0: | 27180207 |
| ETIM 6.0: | EC002499 |
| Basic material: | Sheet steel |





Product features

| | |
|--|---|
| Dimensions: | Width: 600 mm Height: 1800 mm Depth: 600 mm |
| Installation height for components: | 38 U |
| Distance between levels as delivered: | 345 mm |
| Load capacity: | 482.6 mm (19") level: 15000 N |
| Weight/pack: | 75 kg |

Approvals

| | |
|-------------------|--|
| Approvals: |  UL + C-UL (EN) |
|-------------------|--|

Downloads

| | |
|-----------------------|--|
| Data sheets: |  Technical details EN  Technical system catalogue (DE) |
| Documentation: |  Instructions (FR, EN, DE) |
| CAD drawings: |  Visio Shapes (EN, DE) |
| CAD drawings: | Request |