

# Rittal – The System.

Faster – better – everywhere.

## CMC III reader units – DK 7030.220

Date : Aug 12, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP






# CMC III reader units – DK 7030.220

created: 12.08.2016 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Benefits:</b>	Fast connection and automatic detection via plug & play Status display via integral LED
<b>Applications:</b>	For mounting on enclosure doors or next to a room door.
<b>Function principle:</b>	The door is released after authentication by the user. Access rights can be set via the software of the CMC III Processing Unit Power is supplied via connection to the CMC III CAN-Bus Unit Access.
<b>Material:</b>	Plastic
<b>Colour:</b>	Enclosure: RAL 7035 Front: RAL 9005
<b>Protection category IP to IEC 60 529:</b>	IP 30
<b>Supply includes:</b>	CMC III reader units Connection cable Operating manual Compensating panel for TS 8 glazed door design Assembly parts
<b>Packs of:</b>	1 pc(s).
<b>EAN:</b>	4028177659575
<b>Customs tariff number:</b>	83015000
<b>eCl@ss 5.1:</b>	27189253

<b>eCl@ss 7.0:</b>	27189253
<b>ETIM 6.0:</b>	EC002627
<b>Product features</b>	
<b>Design:</b>	Coded lock
<b>Dimensions:</b>	Width: 50 mm Height: 190 mm Depth: 25 mm
<b>Maximum no. of users:</b>	CMC III Processing Unit Compact: 2 CMC III Processing Unit: 16
<b>Operating temperature:</b>	Operation (environment): +0°C...+55°C
<b>Ambient humidity (non-condensing):</b>	Operation (environment): 5 % - 95 %
<b>Equipment (electrical):</b>	Length of connection cable: 3 m
<b>Code:</b>	numerical, max. 8 digits
<b>Weight/pack:</b>	0.28 kg
<b>Approvals</b>	
<b>Declarations:</b>	 <a href="#">Declaration of conformity (DE)</a>
<b>Downloads</b>	
<b>Data sheets:</b>	<a href="#">Graphics (DE)</a>
<b>Documentation:</b>	 <a href="#">Further information</a> EN  <a href="#">Instructions</a> 1 EN
<b>CAD drawings:</b>	<a href="#">Request</a>