

Rittal – The System.

Faster – better – everywhere.

CMC III SMS units – DK 7030.580

Date : Aug 12, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



CMC III SMS units – DK 7030.580



created: 12.08.2016 on www.rittal.com/com-en



Product description

Description:	For configuring a redundant transmission channel or, if there is no network infrastructure available, for alarm forwarding. The alarm signal is designed in SMS format. Power supply is via the processing unit.
Material:	Plastic
Colour:	Front: RAL 9005 Enclosure: RAL 7035
Supply includes:	Connection cable (2 m) with RJ 12 connectors Assembly parts
Note:	The serial interface RS232 of the PU/PUC may only be assigned to one redundant alarm way.
Packs of:	1 pc(s).
EAN:	4028177695917
Customs tariff number:	85176200
eCl@ss 5.1:	27189253
eCl@ss 7.0:	27189253
ETIM 6.0:	EC002627

Product features

Design:	ISDN unit
Requirements for communication connection:	DSS1 (Euro-ISDN) must also be provided when connecting to the ISDN system Point-to-multi-point configuration
Weight/pack:	0.65 kg
Approvals	
Declarations:	 Declaration of conformity (EN, DE)
Downloads	
Documentation:	 Instructions EN
CAD drawings:	Request