

Rittal – The System.

Faster – better – everywhere.

► Cable routing bars, 482.6 mm (19") attachment – DK 7111.214

Date : Aug 11, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Cable routing bars, 482.6 mm (19") attachment – DK 7111.214

created: 11.08.2016 on www.rittal.com/com-en



Product description

Description: For structured routing of entire cable bundles, the cable bars may be secured to a variety of different positions inside the enclosure.

Applications: For horizontal cable routing within the distributor level. Thanks to their open mounting holes, they can also be retrospectively slotted onto the 482.6 mm (19") system punchings of the mounting level at any time and secured with the existing mounting screws of the installed components.

Material: Support: Sheet steel
Cable routing bars, connection combs: Plastic

Colour: RAL 9005

Supply includes: Cable routing bars, 482.6 mm (19") attachment
Connection combs

Note: Size of individual chambers (WxD) approximately 34 x 80 mm

Packs of: 10 pc(s).

EAN: 4028177550360

Customs tariff number: 73269098

eCl@ss 5.1: 27189224

eCl@ss 7.0: 27400604

| | |
|------------------|----------|
| ETIM 6.0: | EC000322 |
|------------------|----------|

Product features

| | |
|---------------|-----|
| Units: | 1 U |
|---------------|-----|

| | |
|------------------------------------|---|
| Number of connection combs: | 5 |
|------------------------------------|---|

| | |
|---------------------|---------|
| Weight/pack: | 0.67 kg |
|---------------------|---------|

Downloads

| | |
|-----------------------|---|
| Documentation: |  Instructions (FR, NL, IT, ES, DE, EN) |
|-----------------------|---|

| | |
|----------------------|---------|
| CAD drawings: | Request |
|----------------------|---------|
