Rittal – The System.

Faster – better – everywhere.

Second pair of mounting angles – DK 7297.000

Date : Aug 10, 2016



ENCLOSURES

POWER DISTRIBUTION >> CLIMATE CONTROL

FRIEDHELM LOH GROUP

Second pair of mounting angles – DK 7297.000 created: 10.08.2016 on www.rittal.com/com-en



Description:	To accommodate 482.6 mm (19") network components or for the attachment of component shelves and slide rails. 482.6 mm (19") punched profile at the front, hole centre distance 465 mm (470 mm at the rear), tailored to the attachment of patch panels and cable routing rails. The mounting level may be positioned on a 50 mm pitch pattern. Minimum distance between levels 150 mm, maximum distance between levels 350 mm.
Material:	Sheet steel, 2 mm
Colour:	Profile frame: RAL 7035 Trim panel: RAL 5018
Supply includes:	Torsionally stiff profile frame Mounting accessories
Packs of:	1 pc(s).
EAN:	4028177128811
Customs tariff number:	94039010
eCl@ss 5.1:	27189207
eCl@ss 7.0:	27182590
ETIM 6.0:	EC002620

Units:	36 U
Installation dimensions:	Installation width: 482,6 mm / 19"
Weight/pack:	12.66 kg
Downloads	
CAD drawings:	Request