

Rittal – The System.

Faster – better – everywhere.

Earth rail, vertical for TS – DK 7544.000

Date : Aug 11, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Earth rail, vertical for TS – DK 7544.000

created: 11.08.2016 on www.rittal.com/com-en



Product description

Description: Easily fitted to the 25 mm DIN pitch pattern of distributors or to the 482.6 mm (19") mounting angles. The supplied earth conductors facilitate star earthing of the cable clamp straps in the patch panels. The earth terminals are fully adjustable. Current carrying capacity of rail approx. 200 A.

Supply includes: Earth rail made from E-Cu 57 to DIN EN 12 163, DIN EN 13 601, 15 x 5 mm
16 conductor connection clamps 2.5 – 16 mm²
15 earthing leads 6 mm², L = 500 mm
Assembly parts

Packs of: 1 pc(s).

EAN: 4028177131859

Customs tariff number: 74199990

eCl@ss 5.1: 27189215

eCl@ss 7.0: 27149205

ETIM 6.0: EC000329

Product features

To fit: Enclosure type: TS
Height: = 1400 mm

Dimensions: Length: 1145 mm

Weight/pack: 2.22 kg

Downloads

Documentation:  [Info sheet \(EN, DE\)](#)

CAD drawings: Request
