

Rittal – The System.

Faster – better – everywhere.

► **Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7709.735**

Date : Aug 9, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7709.735

created: 09.08.2016 on www.rittal.com/com-en



Product description

Description:	Wall-mounted enclosure with optimum accessibility due to hinged part.
Material:	Wall and hinged part: Sheet steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm
Surface finish:	Powder-coated
Colour:	Wall and hinged part: RAL 7035 Glazed door: RAL 7035/7015 (slate grey)
Protection category IP to IEC 60 529:	IP 54 in conjunction with solid gland plate
Supply includes:	Wall section Hinged part with 25 mm pitch pattern of holes in the front and rear frame Designer glazed door Wall section: Gland plate, solid, top Wall section: Gland plate with brush strip, bottom Wall section: 2 vertical punched rails Wall section: C rail mounted horizontally for cable clamping Hinged part with two 482.6 mm (19") mounting angles, fully depth adjustable Hinged part: Side outlet filters left and right Earth rail with star earthing 4 wall mounting brackets 10 mm Mini-comfort handle Security lock 3524 E
Note:	Enclosure 673 mm deep with reinforced wall mounting bracket
Packs of:	1 pc(s).

EAN:	4028177324237
Customs tariff number:	94032080
eCl@ss 5.1:	27180204
eCl@ss 7.0:	27180208
ETIM 6.0:	EC000261
Basic material:	Sheet steel

Product features

Design:	Pre-configured
Dimensions:	Width: 600 mm Height: 478 mm Units: 9 U Depth: 573 mm
Depth hinged part:	416 mm
Installation depth:	520 mm
Clearances:	Clearance width: 502 mm Clearance height: 415 mm
Wall section:	Depth: 135 mm
Load capacity:	Hinged part, static (max.): 45 kg
Weight/pack:	35 kg

Approvals

Approvals:	 UL + C-UL (EN)
-------------------	--

Downloads

Data sheets:	 Technical details EN
Documentation:	 Instructions (EN, DE)
CAD drawings:	Request