

# Rittal – The System.

Faster – better – everywhere.

► **Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7721.535**

Date : Aug 9, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wall-mounted enclosures EL, 3-part pre-configured with mounting angles, depth-variable – DK 7721.535

created: 09.08.2016 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Description:</b>	Wall-mounted enclosure with optimum accessibility due to hinged part.
<b>Material:</b>	Wall and hinged part: Sheet steel, 1.5 mm Viewing window: Single-pane safety glass, 3 mm
<b>Surface finish:</b>	Powder-coated
<b>Colour:</b>	Wall and hinged part: RAL 7035 Glazed door: RAL 7035/7015 (slate grey)
<b>Protection category IP to IEC 60 529:</b>	IP 54 in conjunction with solid gland plate
<b>Supply includes:</b>	Wall section Hinged part with 25 mm pitch pattern of holes in the front and rear frame Designer glazed door Wall section: Gland plate, solid, top Wall section: Gland plate with brush strip, bottom Wall section: 2 vertical punched rails Wall section: C rail mounted horizontally for cable clamping Hinged part with two 482.6 mm (19") mounting angles, fully depth adjustable Hinged part: Side outlet filters left and right Earth rail with star earthing 4 wall mounting brackets 10 mm Security lock 3524 E Comfort handle and 2-point locking
<b>Note:</b>	Enclosure 673 mm deep with reinforced wall mounting bracket
<b>Packs of:</b>	1 pc(s).

<b>EAN:</b>	4028177551039
<b>Customs tariff number:</b>	94032080
<b>eCl@ss 5.1:</b>	27180204
<b>eCl@ss 7.0:</b>	27180208
<b>ETIM 6.0:</b>	EC000261
<b>Basic material:</b>	Sheet steel



## Product features

<b>Design:</b>	Pre-configured
<b>Dimensions:</b>	Width: 600 mm Height: 1012 mm Units: 21 U Depth: 673 mm
<b>Depth hinged part:</b>	516 mm
<b>Installation depth:</b>	620 mm
<b>Clearances:</b>	Clearance width: 502 mm Clearance height: 949 mm
<b>Wall section:</b>	Depth: 135 mm
<b>Load capacity:</b>	Hinged part, static (max.): 75 kg
<b>Weight/pack:</b>	61 kg

## Approvals

<b>Approvals:</b>	 <a href="#">UL + C-UL (EN)</a>
-------------------	--

## Downloads

<b>Data sheets:</b>	 <a href="#">Technical details</a> EN
<b>Documentation:</b>	 <a href="#">Instructions (EN, DE)</a>
<b>CAD drawings:</b>	Request