

Rittal – The System.

Faster – better – everywhere.

PDU international, switched version – DK 7955.334

Date : Aug 12, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



PDU international, switched version – DK 7955.334

created: 12.08.2016 on www.rittal.com/com-en



Product description

Description: Measurement function per phase and individually switchable output slots. Thanks to the compact PDU, any IT rack may be easily equipped with a professional power distribution system. With the TS IT rack, assembly is even tool-free. The compact design allows simple assembly. The installed bistable relays and OLED display keep energy consumption low. An integrated web server can be used as a direct network connection with extensive user administration. Redundant power is supplied from all phases and via an existing Power over Ethernet network. The PDU offers extensive management and monitoring functions. A measuring accuracy of up to 1% guarantees reliability.

Material: Aluminium section, black anodised

**Protection category
IP to IEC 60 529:** IP 20

Standards: EN 60 950-1
IEC 61 000-4
IEC 61 000-6
EN 55 022

Supply includes: incl. connection cable H05-VV (3 m) with fitted input connector







Packs of: 1 pc(s).

EAN: 4028177685246

**Customs tariff
number:** 85369085

eCl@ss 5.1: 27143401

eCl@ss 7.0: 27142604

ETIM 6.0:	EC000330
Product features	
Design:	PDU, switched
Sockets:	36 x IEC 320 socket C13 - Black 6 x IEC 320 socket C19 - Black
To fit:	Enclosure type: TS IT Enclosure type: TS 8 Height: ≥ 2200 mm
Dimensions:	Width: 44 mm Depth: 85 mm Length: 2065 mm
Infeeds:	Qty.: 1 Phases per infeed: 3~
Length of connection cable:	3 m
Ambient conditions:	Operating temperature: +0°C...+45°C Storage temperature: -25°C...+70°C Ambient humidity (non-condensing): 10 % - 95 %
Circuit-breaker 16 A (qty.):	6
Type of electrical connection:	CEE
Rated current (max.):	32 A
Weight/pack:	10 kg
Approvals	
Declarations:	 Declaration of conformity (EN, DE)
Downloads	
Data sheets:	 Technical details EN  Technical system catalogue (DE)
Documentation:	 Instructions EN  Safety instructions
CAD drawings:	 Visio Shapes (EN, DE)

Drivers/software: Software
EN, DE

CAD drawings: Request
