

Rittal – The System.

Faster – better – everywhere.

▶ **Slave PDU international, managed version – DK 7955.932**

Date : Aug 12, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Slave PDU international, managed version – DK 7955.932

created: 12.08.2016 on www.rittal.com/com-en



Product description

Description: Up to 3 slave PDUs can be connected to a PDU managed. Thanks to the compact PDU, any IT rack may be easily equipped with a professional power distribution system. With the TS IT rack, assembly is even tool-free. The compact design allows simple assembly. The installed bistable relays display keep energy consumption low. Redundant power is supplied from all phases. PDU offers extensive management and monitoring functions. A measuring accuracy of up to 1 % guarantees reliability.

Material: Aluminium section, black anodised

**Protection category
IP to IEC 60 529:** IP 20

Standards: EN 60 950-1

Packs of: 1 pc(s).

EAN: 4028177685505







**Customs tariff
number:** 85369085

eCl@ss 5.1: 27143401

eCl@ss 7.0: 27142604

ETIM 6.0: EC000330

Product features

Sockets:	24 x IEC 320 socket C13 - Black 6 x IEC 320 socket C19 - Black
To fit:	Enclosure type: TS IT Enclosure type: TS 8 Height: ≤ 1800 mm
Dimensions:	Width: 44 mm Depth: 85 mm Length: 1450 mm
Infeeds:	Qty.: 1 Phases per infeed: 3~
Length of connection cable:	3 m
Ambient conditions:	Operating temperature: +0°C...+45°C Storage temperature: -25°C...+70°C Ambient humidity (non-condensing): 10 % - 95 %
Type of electrical connection:	CEE
Rated current (max.):	16 A
Weight/pack:	6 kg
Approvals	
Declarations:	 Declaration of conformity (EN, DE)
Downloads	
Data sheets:	 Technical details EN  Technical system catalogue (DE)
Documentation:	 Instructions EN  Safety instructions
CAD drawings:	 Visio Shapes (EN, DE)
CAD drawings:	Request