



# VMS-CMB-E-MZ

### 1080p ULTRA WDR MICRO BULLET IP CAMERA



The compact bullet VMS-CMB-E-MZ is a feature rich camera offering 1080p resolution.

With Ultra Wide Dynamic range and superior low light performance this IP66 camera is ideal for external applications. Coupled with a 3-10.5mm vari-focal lens and a IR Illuminator the bullet camera offers exceptional value for money.

The camera supports motion detection, privacy masking, microSD support and is a true day/night camera.

## **KEY FEATURES**

- 1080p Resolution
- Sony Progressive Scan CMOS Sensor
- Quad Streams Support
- Dual Streams-Full HD 1080P Real-time + H.264 MJPEG D1
- Dual Stream Compression- H.264 Baseline / Main / High Profile + MJPEG
- Multi-language Support
- Tampering Alarm
- Ultra Dynamic Range
- Motion Detection
- Privacy Masks

3D Noise Reduction / 2D Noise Reduction

- Smart IR Mode
- Network Failure Detection
- Day/Night (ICR)
- IR LED Module (working distance up to 15m)
- Digital Image Stabilization (DIS)
- IP66 Rated
- microSD Support
- ONVIF Support



	VAC CAAD E A	T 1000 LU TRA WOR MICRO PLULET ID CAMERA
	VIVIO-CIVID-E-IV	IZ-1080p ULTRA WDR MICRO BULLET IP CAMERA
Image Sensor		1/2.8" ProgressiveCMOS
Effective Pixels		1920(H) x 1080(V)
Minimum Illumination		TBD
Shutter Speed		1 ~ 1/10000 sec.
Lens		
Lens		Vari-focal lens
FocalLength		3-10.5mm
F Number		F1.4
FOV		Wide: 93.2°, Tele: 31.9°
Operation		
Multiple Languages		English/French/German/Italian/Korean/Simplified Chinese/Traditional
	Backlight Compensation	On / Off
	White Balance	Auto / Manual / ATW / Indoor / Outdoor
	Noise Reduction 3D/2D	Low / Middle / High / Off
	Wide Dynamic Range	Shutter WDR (120dB)
	Privacy Mask	On / Off
	Brightness	Manual
	Exposure	Auto / Manual
	Sharpness	Manual
Image Setting	Contrast	Manual
	Saturation	Manual
	Hue	Manual
	Digital Zoom	Support
	Motion Detection	On / Off / By Schedule
	Privacy MaskType	Colour
	ICR	Auto / On / Off / Smart
	ICR+IR LED	Auto / LED On / LED Off / Smart IR / Light Sensor
	Tampering Alarm	On / Off/ By Schedule
Network		
Interface		RJ-45, 10/100/1000 Mbps Ethernet (Giga Ethernet)
Video Compression		H.264 (MJPEG-4 Part 10/AVC)/ MJPEG
Video Streaming	Dual Streams	PAL:H.264 1080P(50 fps) + H.264/MJPEG D1(50 fps) NTSC: H.264 1080P(60 fps) + H.264 D1 (30 fps)
	Quad Streams	H.264 1080P(25/30 fps) + H.264 720P(25/30
	Quad Streams	fps) + H.264 720P(25/30 fps) + H.264/MJPEG
Video Resolution	Quad Streams	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR)
Video Resolution Protocol	Quad Sticums	
	Quita Sileums	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR)
Protocol Security/Authorization	Input	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X  1 Set 5V 10kΩ pull up
Protocol Security/Authorization Alarm		Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPOE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X 1 Set 5V 10kΩ pull up 1 Set Photo Relay Output 300V DC/AC
Protocol Security/Authorization Alarm Event Notification	Input	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X 1 Set 5V 10kΩ pull up 1 Set Photo Relay Output 300V DC/AC HTTP / FTP / SMTP
Protocol Security/Authorization Alarm Event Notification Micro SD	Input	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X 1 Set
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser	Input	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X 1 Set 5V 10kΩ pull up 1 Set Photo Relay Output 300V DC/AC HTTP / FTP / SMTP microSDHC 32GB support Internet Explorer (6.0+) / Chrome / Firefox / Safari
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account	Input	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X 1 Set 5V 10kΩ pull up 1 Set Photo Relay Output 300V DC/AC HTTP / FTP / SMTP microSDHC 32GB support Internet Explorer (6.0+) / Chrome / Firefox / Safari 20
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account PasswordLevels	Input	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X 1 Set 5V 10kΩ pull up 1 Set Photo Relay Output 300V DC/AC HTTP / FTP / SMTP microSDHC 32GB support Internet Explorer (6.0+) / Chrome / Firefox / Safari
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account	Input Output	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X 1 Set SV 10kΩ pull up 1 Set Photo Relay Output 300V DC/AC HTTP / FTP / SMTP microSDHC 32GB support Internet Explorer (6.0+) / Chrome / Firefox / Safari 20 User and Administrator
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account PasswordLevels Mechanical	Input Output  Working Distance	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPOE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X 1 Set
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account PasswordLevels	Input Output  Working Distance Wavelength	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPOE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X 1 Set
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account Password Levels Mechanical Built-in IR Illuminator	Input Output  Working Distance	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPOE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X  1 Set
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account Password Levels Mechanical Built-in IR Illuminator Power Connection	Input Output  Working Distance Wavelength	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPOE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X 1 Set SV 10kΩ pull up 1 Set Photo Relay Output 300V DC/AC HTTP / FTP / SMTP microSDHC 32GB support Internet Explorer (6.0+) / Chrome / Firefox / Safari 20 User and Administrator  up to 25m 850nm 3 PoE & DC Jack
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account Password Levels Mechanical Built-in IR Illuminator	Input Output  Working Distance Wavelength Number of LEDs	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPOE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X 1 Set
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account Password Levels Mechanical Built-in IR Illuminator Power Connection	Input Output  Working Distance Wavelength Number of LEDs	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPOE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X  1 Set
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account PasswordLevels Mechanical Built-in IR Illuminator Power Connection LED Indicator	Input Output  Working Distance Wavelength Number of LEDs  Type Alarm	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X  1 Set
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account Password Levels Mechanical Built-in IR Illuminator Power Connection	Input Output  Working Distance Wavelength Number of LEDs  Type Alarm Power	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X  1 Set
Protocol Security/Authorization Alarm Event Notification Micro SD Supported WebBrowser User Account PasswordLevels Mechanical Built-in IR Illuminator Power Connection LED Indicator	Input Output  Working Distance Wavelength Number of LEDs  Type Alarm	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF / QCIF @50/60fps or 25/30fps (2 shutter WDR) IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, HTTPS / IP Filter / IEEE 802.1X  1 Set

General	
Operating Temperature	-10°C ~ 50°C (14° ~ 122° F)
Humidity	10% ~ 90%, No Condensation
Weatherproof Standard	IP66
Dimensions	Vari-Focallens
Dimensions	Outdoor w/ cable management: Ø 71.5 x150.53 x 91.15 mm (Ø 2.815 x 5.92 x 3.58in.)
Weight	360 g
PowerSource	PoE / DC12V
Power Consumption	System: 5.5 W (Built-in IR Illuminator: +1W)
Regulatory	FCC/ EMC/ LVD /RoHS

Product specification and availability are subject to change without notice.

#### **NSW** - Silverwater

Unit 4, 52 Holker Street Silverwater NSW 2128

E: vmssales@opticalsolutions.com.au

P: +61 2 9395 1400 F: +61 2 9647 0014

#### **NSW - Sydney City**

Unit 10, 10 Bradford Street Alexandria NSW 2015 E: vmssales@opticalsolutions.com.au

P: +61 2 9304 4555

F: +61 2 9700 8055

#### VIC

Unit 3 / 1 Rocklea Drive Port Melbourne VIC 3207

E: vmssales@opticalsolutions.com.au

P: +61 3 9646 4166 F: +61 3 9646 4155

#### QLD

Unit 2/40 Borthwick Ave Murarrie QLD 4172

E: <u>vmssales@opticalsolutions.com.au</u>

P: +61 7 3399 5280 F: +61 7 3399 9805

#### **ACT**

22 Isa Street Fyshwick ACT 2609

E: vmssales@opticalsolutions.com.au

P: +61 2 6162 4600 F: +61 2 6162 4605

#### WA

28a Teddington Rd Burswood WA 6100

E: vmssales@opticalsolutions.com.au

P: +61 8 9361 7000 F: +61 8 9361 7011

