






\*Image is for illustration purpose only



**Top Panel** 2off 130 x 448mm 6off 100 x 100mm 4off 60mm diameter DATA SHEET



**DESCRIPTION:** 

**CABINET DIMENSION:** 

COLOUR: WEIGHT: SHIPPING DIMENSION: SHIPPING WEIGHT: iQ Cabinet - 47RU 600W 1090D

2166H x 600W x 1090D (refer next page for full dimensions details) Black 120Kg 2206H x 640W x 1130D 124Kg

# FEATURES:

- Perforated front door with a curved profile to provide greater surface area and allow more coverage and higher air flow rating
- Screwless integrated Electrical Grounding (Roof, Sides, Doors & Frame)
- Tooless vertical mounting rail, alignment feature integrated into the cabinet for quick alignment
- Large cable access points in the roof provides access for overhead cable egress
- The bottom design allows for unobstructed cable access through a raised floor
- Roof can be removed for access during installation
- Roof is reversible to reposition the larger cable entries for power distribution plugs and connectors
- Cabinets are aisle containment ready for flexible solutions such as vertical air dams, mass cable management and base plates
- Available in black (standard), light grey or white (upon request

with MOQ)

## STANDARD INCLUSIONS:

- Curved perforated front door
- Split rear perforated door
- Split side panels
- Top panel
- · Front and rear mounting rail
- Levelling feet



# **IQS6047V**

DATA SHEET

### **CONSTRUCTION:**

#### Frame:

- A proven frame design and heavy-gauge mounting rails
- Static load ratings 1400 kg (on levelling feet)
- Dynamic load ratings 1000 kg (with castors)

#### Mounting rails and brackets:

- Tooless vertical mounting rails can be adjusted covering virtually any mounting equipment
- RU positions are numbered front and back for quick installation


#### Doors:


- Split rear doors improve access and serviceability to rear of rack mounted equipment
- Simple lift off design front door swing to 155°
- Front door can be moved to the opposite side or interchanged with rear doors
- Doors fitted with swing handle and lock

**DIMENSIONS:** 

#### Side Panel:

- Half height quick release side panels reduce size and weight for easy handling and access
- Side panels are lockable using a single key provided
- Privacy panel options available via pass through holes and brush strips for mounting cabling to adjacent racks





| Cabinet | Width      | Depth (side view image) |                 |
|---------|------------|-------------------------|-----------------|
| RU      | Width (mm) | Frame to<br>Frame       | Door to<br>Door |
| 47RU    | 600        | 1000                    | 1090            |
|         | 600        | 1200                    | 1290            |
|         | 800        | 1000                    | 1090            |
|         | 800        | 1200                    | 1290            |

| Cabinet | Height (front view image) |                      |            |
|---------|---------------------------|----------------------|------------|
| RU      | On Frame                  | On Levelling<br>Feet | On Casters |
| 47RU    | 2166                      | 2188                 | 2216       |