



Microduct Assembly 14/10 mm

TWD 14/10 mm 2-7 way TIA598

Features

- For direct burial
- 2, 4 or 7 bundled ducts
- 14/10 mm microducts
- Low friction inner surface
- Longitudinal grooves for maximum installation lengths

Application

The thick walled microduct are designed with an inner low friction surface that enables installation of micro cables or nano cables. The thick wall of the microducts allow for installation directly into the ground without the need for additional protection.

Design

The duct assemblies are available in several configurations from 2 to 7 microducts. 14/10 mm microducts are optimized for installation of micro cables and nano cables. The microducts have a low-friction inner surface with longitudinal grooves for best blowing performance.

Product Information

Microducts and outer sheath: HDPE

Technical Information

Color Code	TIA598
Temperature, Operation [°C]	-40 to +60
Temperature, Storage [°C]	-40 to +60
Temperature, Installation [°C]	-20 to +50
Conformance	<p>Abrasion: IEC 60794-1-2-E2B(1)</p> <p>Kink: IEC 60794-1-2-E10, 20 x outer diameter</p> <p>Impact: IEC 60794-1-2-E4</p> <p>Crush: IEC 60794-1-2-E3</p> <p>Tensile: IEC 60794-1-2-E</p> <p>Bend: IEC 60794-1-2-E11A</p> <p>Torsion: IEC 60794-1-2-E</p> <p>Flexibility: IEC 60794-1-2-E8</p> <p>Inner Clearance: IEC 60794-5-20, IEC 60794-5-10, Ann. D</p>
Marking	<p>Duct assemblies have markings showing the tube length.</p> <p>The individual microducts are identified by their colours according to the TIA standard.</p> <p>The assemblies come with a white outer sheath, or with a customised outer sheath colour by special order.</p>

Technical Details

TIA-598 Microducts 1-24	1	2	3	4	5	6	7	8	9	10	11	12
	Blue 1	Orange 1	Green 1	Brown 1	Slate 1	White 1	Red 1	Black 1	Yellow 1	Violet 1	Rose 1	Aqua 1
	13	14	15	16	17	18	19	20	21	22	23	24
	Blue 2	Orange 2	Green 2	Brown 2	Slate 2	White 2	Red 2	Black 2	Yellow 2	Violet 2	Rose 2	Aqua 2

TIA 598 Color Code Chart for Microduct Assemblies

Articles

Article name	Color	Layout	Bend Radius [mm]	Tensile Force [N]	Crush [N/100 mm]	Impact [J]	Dimensions [mm]	Weight [kg/km]
Microduct 2x14/10 TWD TIA 5/MPB30281/2CG	White	2x14/10	250	1800	9500	28	29.4 × 15.4	193
Microduct 4x14/10 TWD TIA 5/MPB30277/4CG	White	4x14/10	400	3300	3000	25	29.4 × 29.4	354
Microduct 7x14/10 TWD TIA 5/MPB30277/7CG	White	7x14/10	550	5500	4500	27	43.4	587