Connection Module Cat. 6A EL, 1xRJ45/s, 100x

977803055



The module for the classic office cabling. Easy to install with solid Cat. 6A performance.

The R&Mfreenet Cat. 6A EL connection modules, part of the Freenet cabling system, are ideal for voice, fast data transmissions and high bandwidth applications. This highperformance Cat. 6A module is perfect for use in 10 Gigabit Ethernet (10GBASE-T) and future high-speed applications up to 500 MHz.

PRODUCT_IMAGE

SCOPE OF SUPPLY

- RJ45 Cat. 6A EL connection module, shielded
- Mounting plate
- Dust cover

TENDER

RJ45 connection module of Cat. 6A EL, for the setting up of transmission channels of Class EA with up to 4 connectors acc. to ISO/IEC 11801, EN 50173-1, (DIN EN 50173-1), complies with Cat. 6A requirements of the standards ISO/IEC 11801, EN 50173-1 as well the U.S. standard Cat. 6A according to TIA/EIA 568.2-D, re-embedded tested in acc. with IEC 60603-7-51 and 60512-27-100, interoperable and backwards compatible with Category 6 and Category 5e.

DESCRIPTION

Suitable for 10GBASE-T applications in acc. with IEEE 802.3[™] Section Four up to 500 MHz and 100 m.

Tested in line with R&M's manufacturing control, performing 100% inspection. Each module has an own serial number and is traceable.

Compatible with RJ standard plugs (RJ11, RJ12, RJ45), connection of installation cables AWG 26 22 (0.4 mm 0.65 mm) and flexible cables AWG 26/7 AWG 22/7 without special tools. Parallel pair termination without crossover in acc. with TIA 568-A/B, gold-plated bronze contacts for >1000 mating cycles, IDC contacts with \geq 4 insertion cycles acc. to IEC 60352-3, contact resistance <5 mOhm, dielectric strength >1000 Veff. Supports PoE (IEEE 802.3af), PoEP (IEEE 802.3at), 4PpoE (IEEE 802.3bt) and is compatible to IEC 60512-99-001/002. With integral cable strain relief, including dust cover, nickel plated zinc die-cast housing, ground contacting through 1 contact finger for flat connectors AMP 2.8 x 0.5 mm.

Material: halogen-free and heavy-metal free in acc. with EU directives RoHS 2.

Connection module Cat. 6A EL, die-cast, shielded, dust cover and mounting plate.

GET MORE

- Just two components
- Terminated in just a few steps
- Integrated strain relief
- Installation not requiring specialized knowledge
- Shielded and unshielded
- For all cable types and diameters
- Can be rewired
- · Compatible with common platforms
- Fully tested
- Reliable insulation displacement contacting (IDC)
- Independently certified

R&M warranty program Productive

FEATURES

• Meets the Cat. 6A ISO component specification (for the entire re-embedded plug range as specified by the standards ISO/ IEC 11801, EN 50173, TIA/EIA 568.2-D, IEC 60603-7-51 and 60603-7

- Exceeding the IEEE 802.3 an minimum requements for 10GBASE-T performance
- Achieves best transmission characteristics with R&Mfreenet Cat. 6A patch cables
- · Gold-plated contact area and tin-plated insulation displacement contact area
- Capacitive and inductive compensation
- Compatible with Cat. 6A standard patch cords and cables
- Full mechanical and electrical backward compatibility with Cat. 5e/6
- RJ-11/12/14 compatible
- Fits into 3rd party outlets and patchpanel with 4 different adapter
- Tool-free (w/o special tools) connection of installation cables of AWG 22 26 plus stranded cables of AWG 22/7 26/7
- Wiring option according to TIA 568 A and B with parallel termination of the pairs without splitting of pair 3,6
- Label with color wiring chart, integrated production date and serialnumber (each module) for quality tracing
- Halogen-free materials
- PoE and PoE+ compatible
- 3P certified

TECHNICAL DATA

DESCRIPTION			VALUE / VALUE RANGE		
Category connector (A)			Cat. 6A ISO		
Connector type (A)			RJ45		
Shielding connector (A)			shielded		
Protection class IP			IP 20		
PoE			Yes		
Connector class			connection module		
Wiring diagram			T568A and T568B		
Holder for connector / module			Mounting plate		
Poles			8		
Standard			UL Recognized		
MECHANICAL DATA					
DESCRIPTION			VALUE / VALUE RANGE		
Color			metallic		
ACCESSORIES					
Туре	Picture	Desc	ription	Article	E-Number

Гуре	Picture	Description	Article	E-Number
Accessories		Cable Insert Cat. 6A EL, 4-5 mm Cable	R813797	
Accessories		Copper foil for Module Cat. 6A EL, 100x	R814599	
Accessories		Copper foil for Module Cat. 6A EL, 10x	R824374	

Туре	Picture	Description	Article	E-Number
Accessories		Adapter 90° Module RJ45 C6A-EL/s-10	R833665	966730935