



FIST-GCO2-BD16-NV | 278734-000

FIST™ GC02 Fiber Optic Splice Closure, Heat Shrink Cable sealing, size BD, no pre-installed fiber trays, 16 ports, with test valve

- Single-ended, O-ring sealed dome closure for splicing feeder and distribution cables
- Compatible with most common cable types: e.g. loose tube, central core, ribbon fiber
- Universal mounting system (UMS) profiles provide foundation for mounting combinations of FIST splice trays
- Closure can be used in aerial, pedestal and underground (up to 5 meters) environments
- Compatible with CommScope's CWDM modules and optical splitter trays

Body Features

Cable Seal	Gel Kit (optional) Heat Shrink
Color	Black

Configuration Features

Port Shape	Oval (1) and round (8)
Flash Test Valve	Yes
Number of Pre-installed Splice Trays	none
Slack Basket	Optional

Dimensions

Closure Diameter	247.000 mm 9.724 in
Length	566.00 mm 22.28 in

Packaging Features

Minimum Order Quantity	1
Packaging Method	Box/Carton

Product Availability

Region	EMEA
--------	------

Product Type Features

System	FIST-GCO2
Product Type	Butt Feeder & Distribution Closure

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant