

Rittal – The System.

Faster – better – everywhere.

Component shelf, static installation for 482.6 mm (19") system punchings, depth-variable for TS IT, TE – DK 5501.665

Date : Aug 11, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP




Component shelf, static installation for 482.6 mm (19") system punchings, depth-variable for TS IT, TE – DK 5501.665

created: 11.08.2016 on www.rittal.com/com-en



Product description

Benefits:	Tool-free, time-saving one-man assembly
Applications:	Depth-variable to adapt to individual distances between levels
Material:	Sheet steel
Surface finish:	Spray-finished
Colour:	RAL 9005
Supply includes:	Assembly parts
Packs of:	1 pc(s).
EAN:	4028177679108
Customs tariff number:	73269098
eCl@ss 5.1:	27189218
eCl@ss 7.0:	27189261
ETIM 6.0:	EC002620

Product features	
To fit:	Enclosure type: TS IT Enclosure type: TE 7000 Enclosure type: TE 8000
Dimensions:	Width: 484 mm
Installation options:	482.6 mm (19") L mounting angles, front and rear 482.6 mm (19") mounting frames front and rear
Distance between levels:	min.: 600 mm max.: 900 mm
Units:	0.5 U
Load capacity:	50 kg
Weight/pack:	4.64 kg
Downloads	
Documentation:	 Instructions (FR, EN, DE)
CAD drawings:	Request