

# Rittal – The System.

Faster – better – everywhere.

## ► Component shelf, pull-out 482.6 mm (19") for TS IT, TE – DK 5501.725

Date : Aug 11, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Component shelf, pull-out 482.6 mm (19") for TS IT, TE – DK 5501.725

created: 11.08.2016 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Description:</b>	For mounting between two 482.6 mm (19") mounting levels, on 482.6 mm (19") mounting angles or 482.6 mm (19") mounting frames.
<b>Benefits:</b>	Tool-free, time-saving one-man assembly from the enclosure front Self-locking Fully extendible
<b>Applications:</b>	Depth-variable to adapt to individual distances between levels
<b>Material:</b>	Sheet steel
<b>Surface finish:</b>	Base: Spray-finished Telescopic slides/installation kit: Zinc-plated
<b>Colour:</b>	RAL 9005
<b>Supply includes:</b>	Component shelf, slotted Telescopic slide with mounting kit Assembly parts
<b>Packs of:</b>	1 pc(s).
<b>EAN:</b>	4028177679160
<b>Customs tariff number:</b>	73269098
<b>eCl@ss 5.1:</b>	27189218

<b>eCl@ss 7.0:</b>	27189261
<b>ETIM 6.0:</b>	EC002620
<b>Product features</b>	
<b>To fit:</b>	Enclosure type: TS IT Enclosure type: TE
<b>Dimensions:</b>	Width: 419 mm Depth: 700 mm
<b>Distance between levels:</b>	min.: 600 mm max.: 900 mm
<b>Units:</b>	1.5 U
<b>Load capacity:</b>	100 kg
<b>Weight/pack:</b>	10.72 kg
<b>Downloads</b>	
<b>Documentation:</b>	 <a href="#">Instructions (FR, EN, DE)</a>
<b>CAD drawings:</b>	Request