



6451 5 939-10

Highband® RJ45 Patch Cord, category 6, bag of 2, blue, 1.2 m

Product Classification

| | |
|-----------------------|------------------------------|
| Brand | Highband® |
| Product Series | Highband |
| Product Type | Twisted pair patch cord |
| Regional Availability | Australia/New Zealand EMEA |

Body Features

| | |
|-----------------|----------|
| Cable Color | Blue |
| Shield Style | UTP |
| Conductor Type | Stranded |
| Jacket Material | PVC |

Configuration Features

| | |
|----------------|--------------|
| Configuration | Double-ended |
| Keyed | No |
| Wiring Pattern | T568B |

Dimensions

| | |
|--------------------------------|---------------------|
| Length | 1.20 m 3.94 ft |
| Overall Outside Cable Diameter | 5.400 mm 0.213 in |
| Wire Size (CMA) | 24 AWG |

Industry Standards

| | |
|---------------------|---------------------------|
| Approved Standards | UL 1683 UL 444 (CMR-OF) |
| Flammability Rating | PVC |

Other

| | |
|---------|------------------------------------|
| Comment | Anti-snag feature on RJ plug clip. |
|---------|------------------------------------|

Packaging Features

| | |
|--------------------|-----|
| Packaging Method | Bag |
| Packaging Quantity | 2 |

Product Type Features

| | |
|---------------|--------------|
| Assembly Type | Plug to Plug |
|---------------|--------------|

6451 5 939-10

| | |
|-------------------------|-------------------|
| Connector Type (End A) | RJ45 Modular Plug |
| Connector Type (End B) | RJ45 Modular Plug |
| Performance Category | Category 6 |
| Cable Assembly Category | Industry Standard |
| Cable Type | Twisted Pair |
| Shielded | No |

Usage Conditions

| | |
|-------------------------------|----------------------|
| Operating Temperature Range | -10 – 75 °C |
| Relative Humidity (Operating) | = 93% non-condensing |

Regulatory Compliance/Certifications

| | |
|-----------------|-----------------------|
| Agency | Classification |
| RoHS 2011/65/EU | Compliant |