



6468 5 043-10

LSA-PLUS® Disconnection Module, cat 3, 2/10, PROFIL mounting

Product Classification

Brand	LSA-PLUS®
Product Series	LSA-PLUS
Product Type	Disconnection module
Regional Availability	Australia/New Zealand

Configuration Features

Number of Pairs	10
Number of Reterminations	200

Contact Features

Contact Base Material	Brass
Contact Plating Material	Silver

Electrical Characteristics

Contact Resistance	< 2.5 m Ohms
Current Rating	2 A
Dielectric Strength	2 KV rms
Insulation Resistance	> 50 000 MOhms

Housing Features

Housing Color	White
Housing Material	PBT

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Mechanical Attachment

Mounting Style	PROFIL Rods
----------------	-------------

Other

Comment	For applications in high data rate transmission systems.
---------	--

Packaging Features

Packaging Method	Box/Carton
------------------	------------

6468 5 043-10

Packaging Quantity 10

Product Type Features

Performance Category Category 3

Termination Features

Termination Method IDC

Usage Conditions

Operating Temperature -5 – 60 °C

Relative Humidity (Operating) 95%, no water condensation, no ice

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant