

# Rittal – The System.

Faster – better – everywhere.

## CMC III SMS units – DK 7030.570

Date : Aug 12, 2016

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# CMC III SMS units – DK 7030.570



created: 12.08.2016 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Description:</b>	For configuring a redundant transmission channel or, if there is no network infrastructure available, for alarm forwarding. The alarm signal is designed in SMS format. Power supply is via the processing unit.
<b>Material:</b>	Plastic
<b>Colour:</b>	Front: RAL 9005 Enclosure: RAL 7035
<b>Supply includes:</b>	Connection cable (2 m) with RJ 12 connectors Assembly parts
<b>Note:</b>	The serial interface RS232 of the PU/PUC may only be assigned to one redundant alarm way.
<b>Packs of:</b>	1 pc(s).
<b>EAN:</b>	4028177695900
<b>Customs tariff number:</b>	85176200
<b>eCl@ss 5.1:</b>	27189253
<b>eCl@ss 7.0:</b>	27189253
<b>ETIM 6.0:</b>	EC002627

## Product features

<b>Design:</b>	CMC III GSM unit quad-band
<b>Requirements for communication connection:</b>	A standard, commercially available SIM card for GSM must be provided by the customer.
<b>Covered GSM frequencies:</b>	850 900 1800 1900
<b>Weight/pack:</b>	0.67 kg
<b>Approvals</b>	
<b>Declarations:</b>	 <a href="#">Declaration of conformity (EN, DE)</a>
<b>Downloads</b>	
<b>Documentation:</b>	 <a href="#">Instructions</a> EN
<b>CAD drawings:</b>	Request