



FIST-GCO2-BC6-NV | 739184-000

**FIST™ GC02 Fiber Optic Splice Closure, Heat Shrink Cable sealing, size BC, no pre-installed fiber trays, 6 ports, with test valve**

- Single-ended, O-ring sealed dome closure for splicing feeder and distribution cables
- Compatible with most common cable types: e.g. loose tube, central core, ribbon fiber
- Universal mounting system (UMS) profiles provide foundation for mounting combinations of FIST splice trays
- Closure can be used in aerial, pedestal and underground (up to 5 meters) environments
- Compatible with CommScope's CWDM modules and optical splitter trays

## Body Features

Cable Seal	Gel Kit (optional)   Heat Shrink
Color	Black

## Configuration Features

Port Shape	Oval (1) and round (6)
Flash Test Valve	Yes
Number of Pre-installed Splice Trays	none
Slack Basket	Optional

## Dimensions

Closure Diameter	247.000 mm   9.724 in
Length	488.00 mm   19.21 in

## Packaging Features

Minimum Order Quantity	1
Packaging Method	Box/Carton

## Product Availability

Region	EMEA
--------	------

## Product Type Features

System	FIST-GCO2
Product Type	Butt Feeder & Distribution Closure

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
RoHS 2011/65/EU	Compliant