

GE 300



Compact System Intercom IP-Server GE 300

Compact and suitable for networks, the GE 300 Intercom Server is ideal for Intercom systems where small, manageable units are combined to form a network. Each GE 300 acts as an Intercom IP-Server that controls the different interfaces: interface cards for speech, control and indication functions and communication with other systems such as video systems, door and gate control, telephone systems, and more. The simple modular construction of the basic operating

system enables continuous upgrading for new applications and features. The latest design results in the system being physically compact and conforming to the highest standards of electronic reliability. All kinds of Intercom stations, 2-wire, 4-wire as well as IP-stations, can be connected to the GE 300. Connection of the special GEI 300 interface housing also allows cards from the GE 800 to be used.

1. GE 300

Basic housing including power supply, with five plug-in slots. Up to 40 IP-subscribers (or 20 analogue or 20 digital). One AF input (for music or alarm); two inputs for floating contacts; two relay outputs; configuration via Ethernet or RS 232.

2. GEZ 300

Expansion housing including power supply with 5 plug-in slots. Up to 80 subscribers together with basic housing. Basic housing required.

3. GEI 300

Interface housing with two slots for G8-interface cards. Basic housing required.

Technical Data - Benefits

TECHNICAL DATA

AC power supply:	24 V +/-5% / 40 VA / 16 subscribers
DC power supply:	24 – 35 V / 40 W / 16 subscribers
Emergency power consumption:	200 mAh (without cards) cards: see corresponding data sheet
Power consumption:	minimum (no conversation): 8 VA, maximum (All Call): 40 VA
Frequency range:	50 to 15 kHz (–3 db)
Distortion:	less than 0.9%
Operating temperature range:	0° C to +50° C (32° F to 122° F)
Storage temperature range:	–30° C to +60° C (–22° F to 140° F)
Relative humidity:	20% to 80% not condensing
Measurements of the housing:	310 x 210 x 77.5 mm (12.21 x 8.27 x 3.05 inch)
Weight including package:	GE 300: approx. 2300 g (5 lbs) GEZ 300: approx. 2300 g (5 lbs) GEI 300: approx. 1200 g (2.6 lbs)
Mounting:	Wall mounting
Relay outputs:	max. switching capacity: 60 W / 125 VA, max. switching current: 2A max. switching voltage: 60 VDC / 40 VAC
Music input:	max. 800 mV _{rms} at 10 kΩ, 16 kHz
Inputs IN1, IN2:	for floating contacts, max. line resistance: 1.5 kΩ

EXPANSION

	Subscribers:	Outputs:	Inputs:
Basic expansion:	0	2	2
Maximum expansion:	see "Plug-in Position of the Cards"		

BENEFITS

- Compact plastic housing suitable for wall mounting
- Easy installation and start-up
- More than 150 standard features (a detailed list is available separately)
- Latest Intercom technology
- For all kinds of Intercom stations (IP, digital or analogue)
- Digital networking over IP, 2-wire lines, E1 or ISDN
- Integrated functions for door/gate control, alarms, conferences and central control desks
- Plug&Play CCTV integration
- Flexible expansion by means of different feature packages
- Wide range of applications
- User-friendly configuration with PC software (included in extent of supply)

EXTENT OF SUPPLY

- GE 300: Intercom Server including CD "Software and Manuals" and short reference
- GEZ 300: Expansion housing including short reference
- GEI 300: Interface housing including short reference

The types of GE 300 and GEZ 300 differ in extent of supply:

- GE 300, GEZ 300: without transformer
- GE 300EU, GEZ 300EU: incl. transformer 230 V Europe
- GE 300AU, GEZ 300AU: incl. transformer 230 V Australia
- GE 300US, GEZ 300US: incl. transformer 120 V USA
- GE 300UK, GEZ 300UK: incl. transformer 230 V UK

COMMEND

A strong Partner Network | Worldwide

Europe

SWITZERLAND	Commend AG
:	Tel. +41-44-955 02 22
:	www.commend.ch
FRANCE	Commend France S.A.S.
:	Tel. +33-149 18 16 40
:	www.commend.fr
SPAIN	Commend Iberica S.L.
PORTUGAL	Tel. +34-91-395 24 98
:	www.commend.es
ITALY	Commend Italia s.r.l.
:	Tel. +39-035-95 39 63
:	www.commend.it
NETHERLANDS	Commend Nederland B.V.
BELGIUM	Tel. +31-76-200 01 00
:	www.commend.nl
AUSTRIA	Commend Österreich GmbH
CROATIA	Tel. +43-1-715 30 79
SERBIA	www.commend.at
SLOVENIA	
RUSSIA	
SLOVAKIA	Commend Slovakia spol. s r.o.
CZECHIA	Tel. +421-2-58 10 10 40
:	www.commend.sk
UNITED KINGDOM	Commend UK Ltd
IRELAND	Tel. +44-1279-45 75 10
:	www.commend.co.uk
POLAND	C&C Partners Telecom Sp.z o.o.
:	Tel. +48-65-525 55 55
:	www.ccpartners.pl
SWEDEN	JNT Sound System AB
NORWAY	Tel. +46-8-99 30 60
FINLAND	www.jnt.se
DENMARK	
ISLAND	
GERMANY	Schneider Intercom GmbH
LUXEMBOURG	Tel. +49-211-88285-333
RUSSIA	www.schneider-intercom.de

America

USA	Commend Inc.
CANADA	Tel. +1-201-529-2425
LATIN AMERICA	www.commendusa.com

Asia

CHINA	Commend Business Hub China
:	Isolectra China
:	Tel. +86-21-52 13 19 28
:	www.isolectra.com.cn
MALAYSIA	Commend Business Hub Malaysia
:	Isolectra (M) Sdn Bhd
:	Tel. +603-7846-9988
:	www.isolectra.com.my
SINGAPORE	Commend Business Hub Asia
:	Isolectra Far East Pte. Ltd
:	Tel. +65-6272-2371
:	www.commend.com.sg

Middle East

ISRAEL	Sberlophone Ltd
:	Tel. + 972-4-834 10 32
:	www.sberlophone.co.il

Oceania

AUSTRALIA	Commend Australia
NEW ZEALAND	Tel. +61-3-9755-3947
:	www.commend.com.au

Other countries

:	Commend International GmbH
:	Tel. +43-662-85 62 25
:	www.commend.com



SECURITY AND COMMUNICATION