

Cat 6 UTP Clipsal Style Jack

L1-C6-CLJK-WH

PRODUCT DESCRIPTION:

Layer 1 Cat 6 Clipsal Style ,22-24 AWG solid conductor, 180 degree Jacks are designed for use with Cat 6 UTP cable and are ideal for Ethernet, Fast Ethernet and Gigabit Ethernet network applications. The outlets feature PCB technology which maintains low insertion loss, return loss and cross talk.

Layer 1 Cat6 Clipsal Style Jacks can be terminated using both a Krone & 110 style punch down tool.



KEY FEATURES

- ◆ Terminates with both Krone & 110 Punch Down Tools
- ◆ Compatible with Layer 1 4pair Termination Tool L1-CT-CLJK
- ◆ Combined T568A & T568B colour coding for easy installation
- ◆ IDC Cap keeps the wires firmly in place
- ◆ Fit into Layer 1 wall plates, Clipsal Plates and most standard Australian Standard Flush Plates
- ◆ Designed for 22-24 AWG Solid Conductors
- ◆ ETL verified to ANSI/TIA-568-C.2
- ◆ UL listed
- ◆ ISO/IEC 11801 2nd edition
- ◆ IEC 60603-7
- ◆ AS/CA S008:2010

TECHNICAL SPECIFICATION

| | |
|------------------------------------|---|
| Part Number | L1-C6-CLJK-WH |
| Description | Cat 6 UTP Clipsal Style Jack - 180 Degree w/IDC Cap |
| Colour | White |
| Contacts | Phosphor bronze contacts with 50u" gold plating |
| Insertion Life | 750 mating cycles with FCC compliant plug |
| Durability | 200 termination cycles |
| Operating Temperature Range | -10 deg C to 60 deg C |